



CITY OF WINTER GARDEN
300 WEST PLANT STREET
WINTER GARDEN, FL 34787

P: 407.656.4111
WWW.WINTERGARDEN-FL.GOV

WINTER GARDEN • A charming little city with a juicy past.

RESIDENTIAL SWIMMING POOL, SPA & HOT TUB SAFETY REQUIREMENTS

JOB ADDRESS _____ PERMIT # _____
Contractor _____ Owner's Name _____

As the pool owner, I acknowledge that a new swimming pool, spa, or hot tub will be constructed or installed on my property. I have authorized the following method(s) checked below, to be used /installed meeting the requirements of Florida Statutes for pool safety (F.S.) 515

Owner's Signature _____ Date _____

Pool Protection Only, No Alarms Required

The pool will be equipped with an approved, safety-pool cover that complies with ASTM F1346-91 Standard Performance Specifications for Safety Covers for Swimming Pools, Spas, and Hot Tubs).

Above Ground Pools: R4501.17.1.10: Where an aboveground pool structure is used as a barrier or where the barrier is mounted on top of the pool structure and the means of access is a ladder or steps, the ladder or steps shall either be capable of being secure, locked, or removed to prevent access, or the ladder or steps shall be surrounded by a barrier which meets the requirements of R4501.17.1.1 through R4501.17.1.15. When the ladder or steps are secured, locked, or removed.

48" tall fencing that meets FBC R4501.17.1 – 4501.17.8 with self-closing, self-latching access gates with the release device at min. 54" above grade.

48" tall Removable mesh child safety barrier meeting R4501.17.1.13 and R454501.17.1.15 may be used when inside a pool screen enclosure

Home is Part of The Pool Barrier, Alarms Required

The pool will be isolated from access to the home by an enclosure that meets the pool barrier requirements of F.S. 515.29. (FBC 6th Edition R4502.17.1) Alarms are required

All doors providing direct access from the home to the pool must be equipped with self-closing, self-latching device with a release mechanism placed no lower than 54 inches above the floor or deck.

All doors and windows providing direct access from the home to the pool must be equipped with an exit alarm that has a minimum sound pressure rating of 85 decibels at ten feet.

A swimming pool alarm that, when placed in a pool, sounds an alarm upon detection of an accidental or unauthorized entrance into the water. Such pool alarm must meet and be independently certified to ASTM Standard F2208, titled "Standard Safety Specification for Residential Pool Alarms" which includes surface motion, pressure, sonar, laser or infrared beams. For the purposes of this paragraph, the term "swimming pool alarm" does not include any swimming protection alarm device designed for individual use, such as an alarm attached to a child that sounds when the child exceeds a certain distance or becomes submerged in water.

This is a required form to be submitted with all pool applications as part of the construction plans.

Revised May, 2018